# TERRELL C BIRCH RAYMOND C STEWART JOSEPH A. KOLASCH JAMES M SLATTERY BERNARD L SWEENEY\* MICHAEL K MUTTER CHARLES GORENSTEIN GERALD M MURPHY, JR LEONARD R SVENSSON TERRY L CLARK ANDREW D MEIKLE MARC S. WEINER JOE MCKINNEY MUNCY ROBERT J. KENNEY DONALD J. DALEY JOHN W. BAILEY JOHN V. BAILEY JOHN J. YACURA **E**0

# BIRCH, STEWART, KOLASCH & BIRCH, LLP

INTELLECTUAL PROPERTY LAW 8110 GATEHOUSE ROAD SUITE 500 EAST FALLS CHURCH, VA 22042-1210 USA (703) 205-8000

> FAX. (703) 205-8050 (703) 698-8590 (G IV)

e-mail mailroom@bskb.com web: http://www.bskb.com

CALIFORNIA OFFICE: COSTA MESA, CALIFORNIA THOMAS S AUCHTERLONIE JAMES T. ELLER, JR SCOTT L LOWE MARK J NUELL, Ph D D RICHARD ANDERSON PAUL C. LEWIS MARK W MILSTEAD\* RICHARD J. GALLAGHER JAYNE M SAYDAH\*

JAYNE M SAYDAH\*

REG, PATENT AGENTS:
FREDERICK R HANDREN
MARYANNE ARMSTRONG, Ph D
MAKI HATSUMI
MIKE S. RYU
CRAIG A MCROBBIE
GARTH M DAHLEN, Ph.D.
LAURA C. LUTZ
ROBERT E GOOZNER, Ph.D
HYUNG N. SOHN
MATTHEW J. LATTIG
ALAN PEDERSEN-GILES
C. KEITH MONTGOMERY
TIMOTHYR . WYCKOFF
KRISTI L. RUPERT, Ph.D
LARRY J. HUME
ALBERT LEE
HRAYR A. SAYADIAN, Ph.D

OF COUNSEL
HERBERT M BIRCH (1905-1996)
ELIOT A. GOLDBERG\*
WILLIAM L. GATES\*
EDWARD H. VALANCE
RUPERT J. BRADY (RET )\*
F PRINCE BUTLER
FRED S. WHISENHUNT "ADMITTED TO A BAR OTHER THAN VA

1 m 1 £, 5 Ö E and  $T_{i}$ 

American Ferrina

Date: October 30, 2000

Docket No.: 2950-0175P

Assistant Commissioner for Patents BOX PATENT APPLICATION Washington, D.C.

Sir:

Transmitted herewith for filing is the patent application of

KIM, Byung Jin Inventor(s):

SEO, Kang Soo; YOO, Jea Yong

METHOD FOR SUPPORTING A STILL PICTURE OF DATA STREAM For:

RECORDED IN A DISK RECORDING MEDIUM

#### Enclosed are:

- A specification consisting of 13 pages \_X\_
- 04 sheet(s) of Formal drawings <u>X</u>
- An assignment of the invention <u>X</u>
- Certified copy of Priority Document(s) \_X\_\_
- \_\_\_\_ Original X Photocopy Executed Declaration \_X\_\_
- A verified statement to establish small entity status under 37 CFR 1.9 and 37 CFR 1.27
- Preliminary Amendment
- Information Disclosure Statement, PTO-1449 and reference(s)

Other \_\_\_\_\_

The filing fee has been calculated as shown below:

LARGE ENTITY

SMALL ENTITY

FOR	NO. FILED	NO. EXTRA	RATE	FEE		RATE	FEE
BASIC FEE	********** ******	********	**** *****	\$710.00	or	**** ****	\$355.00
TOTAL CLAIMS	14 - 20 =	0	x18 =\$	0.00	or	x 9 = 3	0.00
INDEPENDENT	5 - 3 =	2	x80 =\$	160.00	or	x 40 = 3	\$ 0.00
MULTIPLE DEPENDENT CLAIM PRESENTED <u>no</u>			+270 =	\$ 0.00	or	+135 = 8	\$ 0.00

TOTAL \$ 870.00

TOTAL \$

0.00

A check in the amount of  $$\frac{910.00}{}$  to cover the filing fee and recording fee (if applicable) is enclosed.

Please charge Deposit Account No. 02-2448 in the amount of \$\_\_\_\_\_. A triplicate copy of this transmittal form is enclosed.

No fee is enclosed.

If necessary, the Commissioner is hereby authorized in this, concurrent, and future replies, to charge payment or credit any overpayment to Deposit Account No. 02-2448 for any additional fees required under 37 C.F.R. 1.16 or under 37 C.F.R. 1.17; particularly, extension of time fees.

Respectfully submitted,

BIRCH, STEWART, KOLASCH & BIRCH, LLP

By\_

Reg. No. 32,644

P. O. Box 747

Falls Church, Virginia 22040-0747

(703) 205-8000 TLC/cqc

The first of that the time will

25

Hall here here

# METHOD FOR SUPPORTING A STILL PICTURE OF DATA STREAM RECORDED IN A DISK RECORDING MEDIUM

#### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates to a data recording method for enabling a digital television to present a part of digital data stream recorded in a disk such as a high-density digital versatile disk (HD-DVD) as a still picture, and a method for providing a digital television with still information based on the recorded data stream.

#### 2. Description of the Related Art

A high-density digital versatile disk (HD-DVD), whose recording standard is under discussion among related companies, is a high-capacity storage device for moving pictures of large 15 size, so that it will be widely used soon. In the meantime, a disk reproducing device (referred as 'HDVD player' hereinafter) which is being developed to reproduce a high-density digital versatile disk is expected to be connected with a digital television through IEEE 1394 standard when it playbacks an inserted disk.

ı

15

When a HDVD player is connected with a digital television to playback a HD-DVD, it should have specific video pictures to be displayed as still images on a screen of a digital television. Examples of the specific video pictures are a 5 background image of menu bars for selection of various functions provided from a HD-DVD, and a menu screen for editing a content scenario of a moving picture program recorded in a HD-DVD.

To embody still picture of data stream recorded in a 10 DVD-ROM which is being popularized more and more, a still mark is written behind a data stream section corresponding to a still picture, and a DVD-ROM player, which can reproduce a DVD-ROM disk, repeats to output the last-decoded stream section if a still mark is detected while reproducing recorded programs.

This method is possible since a DVD-ROM player has been developed in expectation that it is to be connected with an analog television not equipped with a MPEG decoder so that it has a MPEG decoder as an internal component, therefore, a DVD-ROM player can detect still marks contained in data stream 20 while decoding data stream recorded in a DVD-ROM disk.

However, a HDVD-player may not have a MPEG decoder as an internal component since it is under development on assumption that it may be connected a digital television equipped with a MPEG decoder through a digital interface such as IEEE 1394 as 25 aforementioned.

Therefore, even though still marks are inserted in every data stream section corresponding to still picture in a HD-DVD as in a DVD-ROM, a HDVD player can not conduct still operation if it has not a decoder, that is, it can not detect 30 the still mark.

In addition, a digital television developed at present can not support still function for data stream when it receives data stream from a HDVD player connected through a digital

interface, so that it is urgently required to develop a method of presenting a specific data stream section from a disk device such as a HDVD player in a still picture at a digital television.

#### SUMMARY OF THE INVENTION

It is an object of the present invention to provide a method of recording still information, which is identifiable at a digital television, in a high-density disk, and a method for enabling a digital television to present a part of digital stream corresponding to a still picture received through a digital interface such as IEEE 1394 as a still picture based on the furnished still information or data stream.

A still picture supporting method according to the present invention, when recording video data in an optical disk, writes still information indicating that a video data stream section is to be presented as a still picture, and writes information in a cell on whether there is a still picture in a stream object containing the video data stream section wherein the cell is linked with the stream object.

Another still picture supporting method according to the 20 present invention, when recording video data in an optical disk, records video data in a streaming format, and writes a transport packet indicating that a data section among the recorded video data is a still picture at a neighboring side of the data section, wherein the contents of the transport packet is not decoded when 25 reproducing the recorded video data.

Another still picture supporting method according to the present invention, when reproducing data stream recorded in an optical disk comprising recorded video data stream; still information indicating that a video data stream section among 30 the recorded video data stream is to be presented as a still picture; and information written in a cell on whether there is a still picture in a stream object containing the video data

stream section wherein the cell is linked with the stream object, checks whether a video data reproduced from the disk is corresponding to a still picture, and conducts an iteration of transmitting a predictive picture data of the reproduced video data repeatedly after transmitting the reproduced video data based on the checked result.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention, illustrate the 10 preferred embodiments of the invention, and together with the description, serve to explain the principles of the present invention.

In the drawings:

- FIG. 1 shows a digital television and a HDVD player to 15 which a method for supporting a still picture of data stream recorded in a disk according to the present invention is applied;
- FIG. 2 shows a format example of a recorded stream to embody a still picture supporting method according to the 20 present invention;
  - FIG. 3A shows a format example of a recorded stream to embody another still picture supporting method according to the present invention;
- FIG. 3B shows an information example written in a cell 25 associated with a stream object containing a still picture data: and
  - FIG. 4 shows a transmission example of a recorded stream corresponding to a still picture according to another embodiment of the present invention.

#### DETAILED DESCRIPTION OF THE PREFFERRED EMBODIMENTS

In order that the invention may be fully understood, preferred embodiments thereof will now be described with reference to the accompanying drawings.

FIG. 1 shows a digital television 200 and a HDVD player 100 to which a method for supporting a still picture of data stream recorded in a disk according to the present invention is applied. The digital television 200 and the HDVD player 100 are connected each other through a IEEE 1394 digital interface.

The data written in a HD-DVD which is to be playbacked in the HDVD player 100 is grouped into high-density stream objects (called 'HOBs' hereinafter). A HOB may correspond to a single program or a digital stream recorded from recording start to stop, and it is to be associated with each cell which is used for determining the playback sequence of moving picture contents recorded in a HD-DVD.

FIG. 2 shows a format example of a recorded stream to embody a still picture supporting method according to the present invention.

As shown in FIG. 2, the data stream belonging to a certain HOB contains a still packet as still information. The function of a still packet is to command the digital television 200 to repeat to decode a stream constituting a single picture following the still packet instead of advancing the

25 reproduction, and a still packet contains still duration information indicating how long the requested still operation lasts. The still duration is classified into two types of the definite and the indefinite. The definite type may have time value ranging from 1 to 254 seconds, and the indefinite type

30 is used in a condition that a key command from a user is necessary.

When the data stream recorded as in FIG. 2 is reproduced in the HDVD player 100 and is transmitted to the digital

digital bus, the still packet is also transmitted to the digital television 200 without being decoded. When the digital television 200 receives the still packet while decoding the received data stream into real video and/or audio signal, it extracts still duration information from the received still packet. After that, the digital television 100 decodes data stream section, which is following the still packet, corresponding to a single picture and then repeats outputting the just-decoded video picture during the time indicated by the extracted still duration information.

If the time indicated by the still duration information expires, the digital television 200 stops repeating of decoding of same picture, and then resumes to decode next pictures, which 15 may have been already stored in an internal buffering memory, succeeding the still picture.

Through the above-explained operations, a picture can be held as a still picture in a digital television for a certain time.

In the above-explained embodiment of the still picture supporting method, an additional command for holding a picture and resuming successive decoding needs not be sent from the HDVD player 100 to the digital television 200.

Instead of positioning a still packet before a still picture, a still packet may be preceded by a still picture. In this case, the HDVD player 100 may turn its mode into a pause without advancing next pictures as soon as it identifies a packet as a still one based on a packet header. And the digital television 200 repeats decoding a partial data stream, which 30 is received prior to a still packet, constituting a single picture when the received packet is determined as a still one. This interoperation between the HDVD player 100 and the digital television 200 can also achieve still function.

The still packet may not contain information on still duration. Instead, the HDVD player 100 resumes data reproduction from recorded data following the still packet and transmits the reproduced data stream to the digital television 100 if a user requests release of still status. According to the resumption of data reproduction, the digital television 200 receives data packets next to the still packet, then it acknowledges the reception of data packet as release of still picture, and decodes the received data packets as soon as it stops repetition of decoding of one picture.

FIG. 3A shows another format example of a recorded stream to embody a still picture supporting method according to the present invention.

As explained above referring to FIG. 2, the data written in a HD-DVD which is to be playbacked in the HDVD player 100 is grouped into HOBs. A HOB is also corresponding to a single program or a digital stream recorded from recording start to stop, and it is related with each cell which is used for determining the playback sequence of moving picture contents 20 recorded in a HD-DVD.

And, a HOB is composed of high-density stream object units (referred 'HOBUs' hereinafter), and a data stream constituting a HOBU is recorded across a lot of data packs as shown in FIG. 3A. A data pack is a data accessing unit whose size is physically readable and/or writable at a time, that is, it is corresponding to a sector of a DVD-ROM. Each data pack consists of a pack header and several transport packets written in it.

The pack header comprises fields of 'STILL Indicator', 30 'SYS\_PCR\_base', 'SYS\_PCR\_ext, and 'Reserved'. A transport packet may contain a program clock reference (PCR) which consists of a 9-bit extension value and a 33-bit base value according to the MPEG standard. The extension value is a

modulo-300 counter that is incremented at a rate of 27 MHz, whereas the base value is incremented at a rate of 90 KHz. If a transport packet contains a PCR, the PCR is copied to the fields of 33-bit 'SYS\_PCR\_base' and 9-bit 'SYS\_PCR\_ext',

5 respectively. The field of 'STILL Indicator' is a 1-bit flag and is used to indicate whether or not a data pack has data stream to be transmitted repeatedly. That is, if the flag is 1, it means that the pack and following packs including data of Infra-coded picture (I-picture) and predictive pictures 10 (P-pictures) should be transmitted repeatedly.

In addition, a cell associated with a HOB containing one or more still pictures consists of general information and still picture entry point information as shown in FIG. 3B. The general information has various information on reproduction 15 sequence of still pictures, whether there is still picture or not, and the number of still pictures. And, the still picture entry point information has information indicating all of HOBUs in which data stream sections corresponding to still pictures are written. The information on whether there is still picture 20 or not and the number of still pictures is written in 1-byte field of 'Still YES'.

Therefore, when reproducing a HD-DVD, the HDVD player 100 examines information written in a cell to know whether there is still picture and where still picture is written among a lot of HOBUs, and searches for a corresponding HOBU based on the known information. Then, it examines the successive pack headers belonging to the HOBU to know whether the value of 'STILL Indicator' field is 1 or not.

If the value is 1, the HDVD player 100 reads data stream section containing I-picture data and next P-picture data only and then repeats to transmit the read data stream section to the digital television 200 as shown in FIG. 4. The I-picture data is composed of a sequence header, a header of group of

pictures (GOP), and real video data, and the P-picture data is composed of a header and predictive real data.

The transmission ratio of I-picture to P-picture is 1:15.

That is, a I-picture is transmitted once every 15 transmission

5 of P-picture. When transmitting the I-picture repeatedly, the

HDVD player 100 generates a PCR whose value is transporting time

of each transport packet constituting the I-picture, and

inserts it into every packets or every a few packets. When

transmitting P-pictures repeatedly, the HDVD player 100

10 transmits P-picture header only without transmitting

predictive real data.

The information of transmitting repetition duration, i.e., still duration may be written in a cell or a pack header. If this information has been written, the HDVD player 100 resumes next reproduction after stopping the transmitting repetition when the still duration expires, if has not, it resumes next reproduction when a user requests to do that.

In this embodiment of still picture supporting method, the digital television 200 needs not conduct an additional 20 operation for still mode, instead, it just conducts a normal operation to decode the received data stream section provided repeatedly from the HDVD player 100.

The still picture supporting method according to the present invention makes it possible to present a background 25 image of menu bars for selection of various functions provided from a HD-DVD and a menu screen for editing a content scenario of a moving picture program recorded in a HD-DVD as a still picture on a digital television on condition that a HDVD player is delivering real data in the format of data stream to a digital television connected through a digital interface such as IEEE 1394.

The invention may be embodied in other specific forms without departing from the sprit or essential characteristics

thereof. The present embodiments are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than by the foregoing description and all changes which come within the meaning and range of equivalency of the claims are therefore intended to be embraced therein.

#### What is claimed is:

- 1. A method of writing information for supporting still picture of data stream recorded in an optical disk, comprising 10 the steps of:
  - (a) writing still information indicating that a video data stream section is to be presented in a still picture; and
- (b) writing information in a cell on whether there is a still picture in a stream object containing the video data 15 stream section, the cell being linked with the stream object.
  - 2. The method set forth in claim 1, wherein said step (b) further writes information indicating the location of the video data stream section in the cell.
- 3. The method set forth in claim 1, wherein said step (a) 20 writes the still information in a header of a sector in which the video data stream section is written.
  - 4. The method set forth in claim 1, wherein the video data stream section to be presented as a still picture consists of Infra-coded picture data and predictive picture data.
- 5. A disk device comprising recorded video data stream, still information indicating that a video data stream section among the recorded video data stream is to be presented as a still picture, and information written in a cell on whether there is a still picture in a stream object containing the video data stream section wherein the cell is linked with the stream object.
  - 6. The disk device set forth in claim 5, further comprising information indicating the location of the video

data stream section, the location information being written in the cell.


- 7. The disk device set forth in claim 5, wherein the still information is written in a header of a sector in which the video 5 data stream section is written.
  - 8. A method of writing information for supporting still picture of data stream recorded in an optical disk, comprising the steps of:
    - (a) recording video data in a streaming format; and
- (b) writing a transport packet indicating that a data section among the recorded video data is a still picture at a neighboring side of the data section, wherein the contents of the transport packet is not decoded when reproducing the recorded video data.
- 9. A disk device comprising video data recorded in a streaming format, and a transport packet indicating that a data section among the recorded video data is a still picture, wherein the transport packet is written at a neighboring side of the data section and the contents of the transport packet is not decoded when reproducing the recorded video data.
  - 10. A data reproducing method for supporting still picture of data stream recorded in an optical disk, comprising the steps of:
- (a) checking whether a video data reproduced from the 25 disk is corresponding to a still picture; and
  - (b) conducting an iteration of transmitting a predictive picture data of the reproduced video data repeatedly after transmitting the reproduced video data based on the checked result.
- 30 11. The method set forth in claim 10, wherein the iterative transmission ratio of the video data to the predictive picture data is 1:N wherein N is greater than 1.
  - 12. The method set forth in claim 10, wherein said step


- (b) transmits header information only without sending the predictive data when transmitting the predictive picture data repeatedly.
- 13. The method set forth in claim 10, wherein said step 5 (b) conducts the transmitting iteration during still time specified in still information written in the disk.
  - 14. The method set forth in claim 10, wherein said step (b) conducts the transmitting iteration until a user requests release of still mode.

#### ABSTRACT OF DISCLOSURE

The present invention relates to a data recording method for enabling a digital television to present a part of digital stream recorded in a disk such as a high-density digital 5 versatile disk (HD-DVD) as a still picture, and a method for providing a digital television with still information based on the recorded data stream. The still picture supporting method, when reproducing a high-density disk comprising recorded video data stream; still information indicating that a video data 10 stream section among the recorded video data stream is to be presented as a still picture; and information written in a cell on whether there is a still picture in a stream object containing the video data stream section wherein the cell is linked with the stream object, checks whether a video data 15 reproduced from the disk is corresponding to a still picture, and conducts an iteration of transmitting a predictive picture data of the reproduced video data repeatedly after transmitting the reproduced video data based on the checked result. According to the still picture supporting method, it is 20 possible to present a background image of menu bars for selection of various functions provided from a HD-DVD and a menu screen for editing a content scenario of a moving picture program recorded in a HD-DVD as a still picture on a digital television on condition that a HDVD player is delivering real 25 data in the format of data stream to a digital television connected through a digital interface such as IEEE 1394.

FIG. 1





a still packet which may include duration information






FIG. 3B



# FIG. 4



Attorney Docket No.

# BIRCH, STEWART, KOLASCH & BIRCH, LLP

PLEASE NOTE: YOU MUST \*COMPLETE THE FOLLOWING

Insert Title:

P.O. Box 747 • Falls Church, Virginia 22040-0747 Telephone: (703) 205-8000 • Facsimile: (703) 205-8050

### COMBINED DECLARATION AND POWER OF ATTORNEY FOR PATENT AND DESIGN APPLICATIONS

As a below named inventor, I heroby declare that; my residence, post office address and citizenship are as stated next to my name; that I verily believe that I am the original, first and sole inventor (if only one inventor is named below) or an original, first and joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought on the invention children.

Insert Title:	METHOD FOR	SUPPORTI	NG A STILL	PICTURE	OF DATA	STREAM	RE	CORDE	D
Fill in Appropriate	the specification of win	REF CONTROL NEGO	o.MED HUMed here	eto,					
Information -	the specification v	vas filed on						as	
For Use Without	United States App	olication Number _				(if appli	anblal	and/or	
Specification								as PCT	
Attached:	the specification v	vas med on		***************************************			: 8	ind was	
	International App	CT Article 19 on					(if app	licable)	
and then the first wife that									39
Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Company Compan			nd understand the co						
7 6	I acknowledge th	e dury to disclose	Information which i	s material to pat	tentability as defli	ned in Title 31	7, Cod	le of Fede	ral
or deregia or deregia or deregia	Danulations £1.56								
To the second se	thereof, or natented or	described in any i	orinted publication in	any country bei	fore my or our in	rention thereo	for m	ore than o	ПĖ
2.0	year prior to this appl	lcation, that the sat	ne was not in public	use or on sale in	the United States	s of America r	nore ti	han one ye ed before t	ear he
To Profits Or Groups To See	prior to this application	n, that the invention	n has not been paten foreign to the Unit	ed or made the	erica on an abbli	cation filed b	y me	or my les	gal
:	representative or assig	ins more than twel	ve months (six mont)	ns for designs) p	rior to this applica	tion, and that	no at	plication	COT
. L.E	patent or inventor's ce	rtificate on this inv	ention has been filed	in any country b	oreign to the Unit	ed States of M	Detica	prior to u	113
Ē	I hereby claim for	reign priority benef	its under Title 35, Ur	Ited States Code	, §119(a)-(d) of any	y foreign appli	cation	(s) for pate	ent
:	or inventor's certificate	e listed below and h	ave also identified be	low any foreign a	ipplication for pate	ent or inventor	's ceru	ricate navi	ri <u>u</u>
er nome. In definition	I do not know and thereof, or patented or year prior to this applicatio date of this applicatio date of this applicatio representative or assignatent or inventor's ce application by me or many the properties of the properties or inventor's certificate a filing date before tha	t of the application	on which briotish is c	iaimed:					
: :::: :	Prior Foreign Applie					Prio	rity C	laimed	
Insert Priority				7.0 / 7.0	. /00	7	-		
Information:	<u>99-47843</u>	<u> Korea</u>		10/30			<b>X</b> (es	□ No	
(if appropriate)	(Number)	(Country)		(Month/Day	/Year Filed)		62	140	
3 400 3 400 3 400						[			
or categories to the categories of the categorie	(Number)	(Country)	<del></del>	(Month/Day	/Year Filed)	7	(es	No	
	,	· ·				ſ	<b>_</b>		
		- <del>(D</del>		(Month /Day	//Year Filed)		—i ∕es	NO.	
	(Number)	(Country)		farourus 15s2	// ( COI ( (CC))			·	
						-	⊐		
	(Number)	(Country)		(Month/Day	//Year Filed)		és:	No	
	I hereby claim the ben	04 1 Table 25	Markan Cada B	110(a) af any Uni	ad States provisio	nal application	ss(s) lis	sted below	<i>'</i> .
	i hereby claim the ben	ent auger 1 ms 25'	Omteu states Code, 3	rate) or any orm	En atates provisio	прримана.	(-,		
Insert Provisional									
Application(s):	(Application Number)			(Filling D	late)				
(if any)	. , .								
	44 24 14 27 17 17			(Filing L	latal				
	(Application Number)			<del>-</del>					
	All Foreign Application	ons, if any, for any	Patent or Inventor's (	Certificate Filed N	fore than 12 Mont	hs (6 Months f	or De	signs) Prio	t to
	the Filing Date of This	Application:							
	Country		Application Number		Date of Filing (N	fonth/Day/Ye	ar)		
			• •						
Insert Requested									
information:									
(if appropriate)									
	I hereby claim the her	nefit under Title 35,	United States Code,	120 of any Unite	d States and/or Pl	orior United	(s) nsi State:	en below a s and/or l	PCT
	I hereby claim the hat insofar as the subject application in the ma- information which is between the filing date	t matter of each of nner provided by the	ne first paragraph of	Citle 35, United S	tates Code, §112.	I acknowledge	the d	uty to disc	lose
	information which is	material to the pate	miability as defined i	n Title 37, Code o	of Federal Regulati	ions, §1.56 Whi	ich be	came avau	able
	between the filing dat	te of the prior appli	cation and the nation:	if or PC+ internal	noust itties over o	ting approprie	<b>,</b> ,,,		
Insert Prior U.S.									
Application(s):	(Application Number	<del>?)</del>	(Filing Date)		(Status - patento	ed, pendiing, ab	เออสกร	rect)	
(if any)									
	(Application Number	-1	(Filing Date)		(Status - patente	d, pending, at	undo	ned)	
Page 1 of 2	(whiteenon rammer	•,	/ Q						

#### Attorney Docket No.

I hereby appoint the following attorneys to prosecute this application and/or an international application based on this application and to transact all business in the Patent and Trademark Office connected therewith and in connection with the resulting patent based on instructions received from the entity who first sent the application papers to the attorneys identified below, unless the inventor(s) or assignee provides said attorneys with a written notice to the contrary:

Raymond C. Stewart Joseph A. Kolasch Bernard L. Sweeney Charles Corenstein Loonard R. Svensson Andrew D. Meikle Joe McKinney Muncy John W. Balley Gary D. Yacura	(Reg. No. 21,066) (Reg. No. 22,463) (Reg. No. 24,448) (Reg. No. 29,271) (Reg. No. 30,330) (Reg. No. 32,868) (Reg. No. 32,234) (Reg. No. 32,881) (Reg. No. 35,416)	Terrell C. Birch James M. Slattery Michael K. Mutter Gerald M. Murphy. Jr. Terry L. Clark Marc S. Weiner Donald J. Daley John A. Castellano	(Reg. No. 19,382) (Reg. No. 28,380) (Reg. No. 29,680) (Reg. No. 28,977) (Reg. No. 32,644) (Reg. No. 32,181) (Reg. No. 34,313) (Reg. No. 35,094)
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------

Send Correspondence to:

PLEASE NOTE: YOU MUST COMPLETE THE

FOLLOWING:

Figl Name of First For Sole Invantage Invent Name of Enternor Internor Internor Internor Internor Internor Internor Internor Internor Internor Internor

a Insert Chizenship

Full Name of Secure Inventor If any.

Pall Name of Third Inventor, if stry: see above

## BIRCH, STEWART, KOLASCH & BIRCH, LLP

Customer No. 2292 or

P.O. Box 747 • Falls Church, Virginia 22040-0747 Telephone: (703) 205-8000 • Facsimile: (703) 205-8050

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

GIVEN NAME/FAMILY NAME	INVENTOR'S SIGNATURE		DATE*				
Brung-Tin Kim	Bo		Oct . 25, 2000				
Residence (City, State & Country)		CITIZENSHII					
Kyunggi-do, Korea		Republic of Kor					
POST OFFICE ADDRESS (Complete Street Address including City, State & Country) 111-204, Hansol Cheonggu Apt., 110, Jeongja-dong, Bundang-gu, Seongnam, Kyunggi-do, 463-914, Korea							
GIVEN NAME/FAMILY NAME INVENTOR'S SIGNATURE			DATE*				
Rang-500 Seo	4182		at.25,2000				
Residence (City, State & Country)		CITIZENSHI					
Kyunggi-do, Korea	,	Republ	ic of Korea				
POST OFFICE ADDRESS (Complete Street Address including City State & Country) 606-503, Chowon Hanyang Apt., 897-5, Pyungan-dong,							
Dongan-gu, Anyang, 431	-747, Korea		Lavani				
GIVEN NAME/FAMILY NAME	INVENTOR'S SIGNATURE	/	DATE*				
Jea-Young You	Joney 1	hoo	Oct. 24. zon				
Residence (City, State & Country)		CITIZENSHI					
Seoul, Korea		Republic of Korea					
POST OFFICE ADDRESS (Complete Street Address including City, State & Country) C-306, Maebong Samsung Apt., Dogok-dong, Kangnam-gu,							
Seoul, 135-272, Korea	INVENTOR'S SIGNATURE		DATE*				
GIVEN NAME/FAMILI NAME	HAARIA OKO OYOUNI BIRR						
Residence (City, State & Country)		CITIZENSH	IP				
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)							
CIVEN NAME/FAMILY NAME	INVENTOR'S SIGNATURE		DATE*				
Residence (City, State & Country)		CITIZENSH	IIP				
1							
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)							
1							

Page 2 of 2 (Rev. 01/05/2000)

Full Name of Fifth Inversor, if any: age above

\*DATE OF SIGNATURE